

# L60ITP TECHNICAL DATA SHEET (airspray road marking machine)

Dimensions: 200x85x h120 cm; Weight: 240 Kg



Photo doesn't show standard machine.

## Gasoline engine:

- power 9,5 HP
- self-winding pull start
- centrifugal pulley

## Hydraulic drive with:

- 2 motors directly coupled on rear wheels
- lever control: controls forward, **reverse** and neutral gear
- VARIABLE-FLOW PUMP**: guarantees more **safety** for operator and better **performance**. Allows to overcome steep slopes

**Parking brake** on rear wheel

**Swivel front wheel** with stabilizer springs, to stripe very sharp curves. It can be locked or unlocked during the work by a pneumatic control on dashboard. It's also possible to totally remove springs and adjust steering hardness by proper regulator

**Telescopic pointer** for easily following pre-marking or precisely matching existing line

**Engine shut-off safety device** if operator leaves the handlebars

## Pressurized paint tank:

- capacity 60 l or 40 l
- with manual stirrer and cover totally removable for easier and quicker cleaning

**Solvent tank** for flushing of gun and paint hose

## Two-stage two-cylinder compressor:

- flow air rate 515 l/min
- with **pressure limiting valve**

**Automatic paint gun** with line limiter (shroud), mounted on fixed support with gun height adjustable. (*Fixed support can be replaced with pneumatic support or with marking discs. Look at optional*). Standard nozzle for 10-20 cm line

**MAX. LINE WIDTH:** 30 cm

(achievable only with proper optional equipment)



**SPRAYABLE PRODUCTS:** refractive paints, not refractive paints, special paints with antiskid

*Machine is equipped with all safety devices according to EU requirements.*

*Machine conforms to:*

- *EU Directive 2006/42/EC on Machinery*
- *EU Directive 14/68/EU for Pressure Equipment (PED directive)*

## OPTIONAL EQUIPMENT:

### - Electric starting (SUGGESTED OPTIONAL)

- **Light**, for night works.

Attention: it can be used only if striper is equipped with optional Electric starting

### - **Turning light**, for a better visibility of operator on the street. (SUGGESTED OPTIONAL)

Attention: it can be used only if striper is equipped with optional Electric starting

### - **Electronic spacing device** C8000 with:

- possibility to select 8 different skip line patterns
- possibility to record: total metres made (paint+space); total metres striped (only paint); total metres striped (only paint) by each gun
- sound speed alarm: rings when operator works outside range of minimum speed and maximum speed. Min. and max. speeds are adjustable. (Maintaining constant speed is important for getting uniform paint film).

Attention: it can be used only if striper is equipped with optional Electric starting

### - **Trailer with standing driver** (SUGGESTED OPTIONAL)

### - **Trailer with driver seat**

- **Pneumatic support for paint gun (one disc)**, to keep automatic gun always at the same distance from ground, ensuring constant width of the line (SUGGESTED OPTIONAL)

- **Marking discs**, to get a perfect definition of line edges. Useful particularly for concrete surfaces. Available in following widths:

- marking discs for 10-20 cm line
- marking discs for 10-30 cm line

- **Manual paint gun-short with 5 m air hose and 5 m paint hose**, for stenciling (SUGGESTED OPTIONAL)

- **Manual paint gun - long (with extension 40 cm) with 5 m air hose and 5 m paint hose**, for stenciling without bending and standing farther from paint spray

- **Pressurized glass bead system** consisting of:

- glass bead tank. Available capacity: - **pressurized tank capacity 15,5 l**  
- **pressurized conic tank capacity 20 l**  
- **pressurized tank capacity 26 l**
- automatic glass bead gun with adjustable diffuser
- closing delay regulator for bead gun

- **Manual glass bead gun with air hose and bead hose**, for bead application on stenciling.

Attention: it can be used only if striper is equipped with optional Glass bead system

- **Supplementary pressurized tank for paint**. Available capacities: - **pressurized paint tank capacity 15,5 l**  
- **pressurized paint tank capacity 26 l**.



Lever control for forward and reverse running

Electric starting (optional)



Engine shut-off safety device

60 l pressurized paint tank

Supplementary pressurized 15,5 l tank for paint (optional)



Tool box

515 l/min compressor

Adjustable pointer

Swivel front wheel

Manual paint gun with extension 40 cm and 5 m air and paint hoses (optional)



Fixed support

Automatic paint gun with line limiter (shroud)

Solvent tank for flushing of gun and paint hose