L120 TECHNICAL DATA SHEET (airspray road marking machine)

Dimensions: 190x80x h138 cm; Weight: 490 Kg



Photo doesn't show standard machine.

Gasoline engine:

- -power 25 HP
- -electric starting
- -alternator to recharge the battery
- -centrifugal pulley

Light and turning light

Hydraulic drive with:

- -2 motors directly coupled on rear wheels
- -joystick: controls forward, reverse and neutral gear
- -<u>VARIABLE-FLOW PUMP</u>: guarantees more **safety** for operator and better **performance**. Allows to overcome steep slopes

2 parking brakes on rear wheels integrated in the hydraulic motors

Swivel front wheel with stabilizer springs, to stripe very sharp curves. It can be locked or unlocked during the work by a pneumatic control on dashboard. It's also possible to totally remove springs and adjust steering hardness by proper regulator

Trailer with standing driver

Telescopic pointer for easily following pre-marking or precisely matching existing line

Engine shut-off safety device if operator leaves the handlebars

Pressurized paint tank:

- -capacity 120 l
- -made of stainless steel
- -with manual stirrer and cover totally removable for easier and quicker cleaning

Solvent tank for flushing of gun and paint hose

Two-stage two-cylinder compressor:

- -flow air rate 1210 I/min
- -with pressure limiting valve

Automatic paint gun with line limiter (shroud), mounted on fixed support with gun height adjustable. (Fixed support can be replaced with pneumatic support or with marking discs. Look at optional). Standard nozzle for 10-20 cm line

MAX. LINE WIDTH: 90 cm

(achievable only with proper optional equipment)

Electronic spacing device C8000 with:

- -possibility to select 8 different skip line patterns -possibility to record: total metres made (paint+space); total metres striped (only paint); total metres striped (only paint) by each gun
- -sound speed alarm: rings when operator works outside range of minimum speed and maximum speed. Min. and max. speeds are adjustable. (Maintaining constant speed is important for getting uniform paint film).

Allows to control 1 up to 3 guns (if machine is equipped with 3 guns)

SPRAYABLE PRODUCTS: refractive paints, not refractive paints, special paints with antiskid



Machine is equipped with all safety devices according to EU requirements. Machine conforms to:

- ➤ EU Directive 2006/42/EC on Machinery
- ➤ EU Directive 14/68/EU for Pressure Equipment (PED directive)

OPTIONAL EQUIPMENT:

- Second automatic paint gun with independent control to stripe 50 cm or 2 lines at the same time (for example continuous line + skip line) (SUGGESTED OPTIONAL)
- Third automatic paint gun to stripe 90 cm
- Pneumatic support for paint gun (one disc), to keep automatic gun always at the same distance from ground, ensuring constant width of the line (SUGGESTED OPTIONAL)
- Marking discs, to get a perfect definition of line edges. Useful particularly for concrete surfaces. Available in following widths:
 - marking discs for 10-20 cm line
 - marking discs for 10-30 cm line
 - marking discs for 50 cm line. Attention: 50 cm marking discs can be used only if striper is equipped with optional second automatic paint gun
 - marking discs for 90 cm line. Attention: 90 cm marking discs can be used only if striper is equipped with optional third automatic paint gun
- Manual paint gun-short with 7 m air hose and 7 m paint hose, for stenciling
- Manual paint gun long (with extension 40 cm) with 7 m air hose and 7 m paint hose, for stenciling without bending and standing farther from paint spray
- Pressurized glass bead system (SUGGESTED OPTIONAL) consisting of:
 - pressurized conic tank for glass beads capacity 38,5 l
 - automatic glass bead gun with adjustable diffuser
 - closing delay regulator for bead gun
- Second automatic glass bead gun with independent delay regulator (SUGGESTED OPTIONAL)

Attention: it can be used only if striper is equipped with optional Glass bead system

- Third automatic glass bead gun

Attention: it can be used only if striper is equipped with optional Glass bead system

- Manual glass bead gun with air hose and bead hose, for bead application on stenciling


Attention: it can be used only if striper is equipped with optional Glass bead system

- Supplementary pressurized tank for paint. Available capacities: - pressurized paint tank capacity 15,5 l

- pressurized paint tank capacity 26 l

- 26 I pressurized tank and side extension bracket for pre-marking





Macchine Traccialinee Marking Machines